

Model Name	HS-3200
Product Name	HD 12-Channel HD Portable Video Streaming Studio
Video Standard	Full HD
Video Format	1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz
Input Routable / Crosspoint	All 12, repeatable
Video Input	8x SDI, 4x HDMI
Computer Graphic Interface	4 via HDMI
Down-converted output	N/A
Video Output	5x SDI assignable: PGM, PVW, PGM Clean & multiview, Input 1-12 4x HDMI (3x PGM + 1x assignable)
Audio Input	4x Balanced XLR
Audio Output	2x Balanced XLR
Embedded Audio Support	Input up to 16 channels, Output 4 channels
Audio Delay Calibration	Up to 16 frames
A+V switching	Yes
USK	4
DSK	2x DSK support Lumakey & Linear key (Key / Fill)
Picture in Picture	8 (4x PIP, 4x Flex Source)
Logo Insertion	2
Built-in Audio Mixer	N/A
Built-in Monitor Display	17.3" HD TFT LED backlit, 1920x1080 pix
Built-in Intercom & Tally	N/A
Streaming Video Encode	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
Streaming Audio Encode	AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit

Streaming Protocol	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP (Publish)
Streaming Control	Web browser UI for configuration and control Socket commands
Recording File System	FAT, exFAT, NTFS
Recording File Format	MP4
Recording Setting Control	Web UI for system configuration and control
Dimension (LxWxH)	455 x 355 x 134 mm
Weight	17.8 Lbs (8.1 Kg), Reinforce Plastic Case
Accessory	CB-22H/23H/46/47/60/61/62